



FLAMMABLE GAS DETECTOR

Omniguard® model 1100

The Omniguard model 1100 gas detector is designed to detect and measure the presence and level of flammable gases in industrial applications such as Refineries, Drilling and Production platforms, Gas turbines, Chemical plants, Fuel loading facilities, Compressor stations, Waste water treatment facilities, LNG/LPG processing and Storage facilities, Transportation facilities and Manufacturing processes.

The Omniguard model 1100 gas detector is based on well proven sensor technology and has a fast response time, excellent measuring accuracy and long term stability.

The microprocessor controlled functionality and the simple calibration procedure make the Omniguard 1100 gas detector easy to use and to maintain and very reliable in field operation.

The easy to read display and the standard 4-20 mA and HART rev 7 output make installation and operation of the detector quick and easy.

Specifications


General Specifications

Measuring Type	Diffusion	
Measuring Method	Catalytic cell, Semiconductor cell, Thermal conductivity cell	
Detectable Gases	Flammable gases (LNG, LPG, H ₂ , Methane, Buthane etc)	
Measuring Range	Depending on gas	
Accuracy	≤ ±3% / Full range	
Zero Drift	≤ ±2% / Full range	
Response Time	Typical 90% of range in less than 15 sec (dependent on sensor)	
Basic Interface	Analog 4-20mA current interface	
HART Interface	HART rev 7	
Certification	Ex II 2 G, Ex db IIC Gb T4, T5, T6 Classified for use in hazardous locations Class I, Division 1, Groups A, B, C and D hazardous locations. UL Certificate of Compliance E506030 SIL2 SGS TÜV Certificate number: FS/71/220/20/0568	
Protection Class	IP66	
Operating Temperature	Transmitter:	-40° to +80°C (-40° to +176°F)
	Sensor:	Dependent on sensor
Operation Humidity	Transmitter:	5 to 99% RH (non-condensing)
	Sensor:	Dependent on sensor
Pressure Range	90 to 110 kPa	
Max Air Velocity	6 m/s	

Specifications continue on next page...

Key features

- ♣ Wide range of detectable gases
- ♣ HART rev 7 communication as standard
- ♣ Advanced self-test and diagnostics
- ♣ Smart programming and auto calibration
- ♣ 4-20mA output signal
- ♣ Easy in field calibration and maintenance
- ♣ Robust weather- and flame proof enclosure for indoor or outdoor applications
- ♣ Low cost of ownership
- ♣ ATEX, IECEx, SIL2, CE



Omniguard® model 1100

Specifications (continued)


Electrical Specifications

Input Voltage	18-31 VDC Nominal: 24 VDC Ripple voltage: <1 V
Power Consumption	Max. wattage: 4.8W@+24 VDC Max. current: 200 mA@+24 VDC
Current Loop	0-20mA (Source or Sink), 500 ohms max load
Measured Value Signal:	4mA (Zero) to 20 mA (Full range)
Fault:	0mA
HART Fault:	2mA
Maintenance:	3mA
0-100%:	4mA-20mA
100-109%:	20mA-21.4mA
Over 110%:	22mA
Current Loop Ripple & Noise Max	±20 µA
Wiring Requirement	Power CVVS or CVVSB with shield Analog CVVS or CVVSB with shield
Signal Transmission Distance	Analog: 2500 m (8200 ft)
EMC Protection	Complies with EN50270
Mechanical Specifications	
Material	Housing: Aluminium (ALDC) or Stainless steel (316) Sensor: Stainless steel (316)
Weight	1.5 kg (3.3 lbs) (Aluminum) 3.1 kg (6.8 lbs) (SS)
Dimensions	136 (W) x 166 (H) x 110 (D) mm (5.4 (W) x 6.5 (H) x 4.3 (D)) in
Conduit Entry	3/4-14 NPT or M20x1.5
Mounting Holes	Ø 7 ±0.1 (Ø 0.28 in)

Optional Accessories (Art.no.)

Rain Cover, Plastic	27727
Rain Cover, SS (304)	28368
Splash Guard	27728
Collecting Cone	27729
Magnet Bar	27730
Pole Mount	28236

Warranty 2 years (Transmitter) / 1 year (Sensor)



Omniguard 1100DS - Ver 1.3 | EN
© Firefly AB (2021)

Ordering information

Type:	Omniguard® model 1100
Designation:	Flammable gas detector
Ordering number:	1100 - X X X X X X X
Housing material/conduit entry	0 Aluminium, 3/4-14 NPT (white) 1 Stainless steel, 3/4-14 NPT 2 Aluminium, M20x1.5 (white) 3 Stainless steel, M20x1.5
Detectable gas	0 CH ₄ (Methane) 1 C ₄ H ₁₀ (Buthane) 2 C ₃ H ₈ (Propane) 3 H ₂ (Hydrogen) 9 Special gas
Measuring method	0 Semiconductor cell 1 Thermal conductivity cell 2 Catalytic cell
Measuring range	0 0-2000 ppm (C ₄ H ₁₀) 1 0-100% Vol (H ₂) 2 0-100% LEL (CH ₄ , C ₄ H ₁₀ , C ₃ H ₈ , H ₂) 9 Special range
Output signal	0 4-20mA, and HART rev 7
Configuration	0 Standard 1 Remote option
Approvals	0 ATEX, IECEx, SIL2



For information on the specific certifications and approvals each Omniguard® Gas Detector holds please visit:
<https://omniguardbyfirefly.com/gasdetectors>

Firefly AB
Stockholm, Sweden
Phone: +46 (0)8 449 25 00
E-mail: omniguardsales@firefly.se
www.omniguardbyfirefly.se

